PPT

纯铝箔电容器 PURE ALUMINUM FOIL CAPACITOR

Top of the range pure aluminum foil capacitor, with a slightly less bright and slightly softer tonal profile, compared to high-end Silver/ Silver-Gold based PB super capacitors.

The performance of the PPT capacitors has been dramatically enhanced by reducing resonant sonic outputs from the capacitor winding itself. This is achieved by careful selection of the highest quality polypropylene base film combined with thick pure aluminum foil and close control of critical production processes.

A luxury capacitor designed especially for modern high-end tweeters and mid-range drivers.

HIGHLIGHTS

- Silver connect 银链接
- Pure aluminum foil with PP dielectric insulation铝箔
- Featuring terminal leads made from PC-OCC copper (oxygen free)无氧铜
- Featuring extremely low ESR, inductance and dielectric absorption

TECHNICAL INFORMATION

- Non-polarized capacitor无极性
- Non inductive construction结构无感
- Wrapped with polyester adhesive tape
- Ends filled with flame retardant epoxy resin
- Voltage rating: 160 VDC
- Capacitance tolerance : +/- 3% centered on nominal value
- Temperature range: -30℃ to +85℃
- Extremely low ESR and ESL
- Dissipation factor: .0001

RATINGS AND DIMENSIONS:

UNIT: millimeter

VDC / MFD	160VDC OD	160VDC L	250VDC		400VDC		630VDC	
1.0	14	50						
1.5	17	50						
1.8	19	50						
2.0	16	58						
2.2	18	58						
2.7	21	58						
3.0	24	58						
3.3	19	74						
4.0	20	74						
4.7	22	74						
5.6	24	74						
6.8	24	86						
8.2	28	86						
10	30	86						